



PC2.0 SERIES

PEDESTRIAN PALLET TRUCK

TECHNICAL SPECIFICATIONS




A6W9

V1.0

11 September 2026

TRUCK DIAGRAM



TECHNICAL DATA

SPECIFICATIONS TABLE

GENERAL	1.2	MODEL DESIGNATION			PC2.0
	1.1	Manufacturer			HYSTER
	1.3	Drive type			Full-Electric
	1.4	Operator type			Pedestrian
	1.5	Rated capacity/rated load	Q	t	2.0
	1.6	Load centre distance	c	mm	600
	1.9	Wheelbase	y	mm	1197/1267
Weight	2.1	Service weight including battery		kg	119/125.5
Wheels	3.1	Tyres, front/rear			PU (Polyurethane)
	3.2	Tyre size, front		mm	Ø140*55
	3.3	Tyre size, rear		mm	Single wheel: Ø80*93
	3.3	Tyre size, rear		mm	Double wheel: Ø80*70
	3.5	Number of wheels, front/rear (X = driven)			1x+2/4
	3.7	Tread, rear	b11	mm	385/520
Dimensions	4.4	Lift	h3	mm	115
	4.9	Height drawbar in driving position min./max.	h14	mm	820/1150
	4.15	Height, fork lowered	h13	mm	82+2
	4.19	Overall length	l1	mm	1552/1622
	4.20	Length to face of forks	l2	mm	1150/1220
	4.21	Overall width (single / wide / dual)	b1	mm	550/685
	4.22	Fork dimensions (Height*width*length)	s/e/l	mm	58/160/1150 or 1220
	4.25	Distance between fork-arms	b5	mm	550/685
	4.32	Ground clearance, centre of wheelbase	m2	mm	22/137 or 24/13
	4.34.1	Aisle width for pallets 1000 × 1200 crossways	Ast	mm	2376
	4.34.2	Aisle width for pallets 800 × 1200 lengthways	Ast	mm	2257
	4.35	Turning radius	Wa	mm	1353/1426
Performance	5.1	Travel speed, laden/unladen		km/h	4.0/4.5
	5.1.1	Travel speed, laden/unladen, backwards		km/h	4.0/5.0
	5.2	Lift speed, laden/unladen		mm/s	22.5/32.8
	5.3	Lowering speed, laden/unladen		mm/s	40.9/27.3
	5.7	Gradeability, laden/unladen		%	6%/20%
	5.8	Max. gradeability - 1.6 km/h, with / without load		%	6%/20%
	5.10	Traveling brake			Regenerate
		Brake			Electromagnetic
	6.1	Drive motor, S2 60 min rating		kW	DC Brushless1.0Kw
	6.2	Lift motor S3 15% rating		kW	DC 0.8KW
	6.3	Battery according to DIN 43531/35/36 A,B,C, no			No
	6.4	Battery voltage / nominal capacity K5		V/Ah	48V/10Ah/48V/15Ah
	6.5	Battery weight		kg	4.5/5.9
	6.6	Energy consumption acc. to VDI cycle		kWh/h	0.42
Additional Data	8.1	Type of drive unit			Electric
	10.7	Sound level at the driver's ear according to EN 12053		dB	< 70dB

OPTIONS TABLE

AVAILABLE OPTIONS

DESCRIPTION	STANDARD	OPTIONAL
CONSTRUCTION	STANDARD	OPTIONAL
Metal Key Switch Start		X
Keyless Start	X	
Remote Control		X
Pin Code on tiller		X
Galvanization		X
LIFT OPTIONS - FRONT END EQUIPMENT	STANDARD	OPTIONAL
1150mm x 550mm / 21.7" x 45.3" Welded Type - Standard Tip Forks	X	
800mm x 550mm / 21.7" x 32" Welded Type - Standard Tip Forks		X
1150mm x 685mm / 27" x 45.3" Welded Type - Standard Tip Forks		X
1220mm x 685mm / 27" x 48" Welded Type - Standard Tip Forks		X
1000mm x 685mm / 27" x 39" Welded Type - Standard Tip Forks		X
1000mm x 550mm / 39" x 21.7" Welded Type - Standard Tip Forks		X
Load Back Rest		X
Retractable Cargo Belt		X
CHASSIS - DRIVE & STEER TIRES	STANDARD	OPTIONAL
80 x 70mm / 3.14" x 2.7" Tandem Polyurethane Load Wheels		X
80 x 93mm / 3.14" x 3.66" Single Polyurethane Load Wheel	X	
Cast Wheels		X



Hyster Company

Caixa Postal 7367 Greenville, NC 27835-7367 EE. UU.

hyster.com

SAFETY: Hyster® powered industrial trucks meet the design and construction requirements of local standards and regulations for the countries into which they are sold, including ANSI/ITSDF B56 (USA), Machinery Directive 2006/42/EC (EU), AS 2359 (Australia), and NR-11 (Brasil). Where permitted by local law, Yale products sold into countries outside of the EU or USA may be ordered in conformance with EU or USA requirements.

NOTICE: Care must be exercised when operating material handling equipment. Operators must be trained and must read, understand and follow the instructions contained in the operating manual. Products may be shown with optional equipment and/or features not available in all regions. Product performance may be affected by its condition, how it is equipped and the application. Specifications are subject to change without notice. Consult your Hyster® Dealer if any of the information shown is critical to your application.

© 2026 Hyster-Yale Materials Handling, Inc., all rights reserved. HYSTER and HYSTER LOGO are trademarks of Hyster-Yale Materials Handling, Inc.