



STRONG PARTNERS. TOUGH TRUCKS.™

# P2.OUTE ELECTRIC WALKIE FORKLIFT

**WWW.HYSTER.COM** 

## P2.OUTE OVERVIEW

The Hyster® electric walkie pallet truck P2.0UTE combines ergonomic features and reliable performance with energy efficient technology. The low-maintenance helps increase productivity and reduce operational costs.

#### STANDARD FEATURES

- Brushless maintenance free AC motor
- Sealed maintenance free batteries
- Small turning radius 1335mm-1405mm (width 520/550/685mm)
- Self-adjusting caster wheels
- Drive capability when tiller is upright, greatly reducing turning space
- Tiller head with max. speed limit button
- Emergency stop and belly button
- Casters to increase stability
- Exit roller
- BDI and hour meter
- Built-in charger

#### **OPTIONS**

- · External charger
- · Various fork widths and lengths available




Handle (Standard) (Left & Right Handed)




Entry roller for easy operation

#### **TURNING RADIUS**

The P2.0UTE has a small turning radius. When switched to low speed it adapts to narrow spaces. Ideal for shipping containers and tailgate applications.




MINI Type Pallet Truck




Hand Pallet Truck

## SPECIFICATIONS AND DIMENSIONS <








MODEL	MEASUREMENT	P2.0UTE
Load capacity	Q (kg)	2000
Load center distance	c (mm)	600
Fork height, lowered	h13 (mm)	85 / 75
Tire size, front	mm	195x70
Tire size, rear (single)	mm	80x93 / 74x93
Tire size, rear (double)	mm	80x70 / 74x70
Wheels number front rear (x = driven wheels)		1X-2/4
Max. lift height	h3 (mm)	190/180
Height of tiller in drive position min./max.	h14 (mm)	950/1310
Overall length	I1 (mm)	1525/1595
Length to face of forks	I2 (mm)	375
Overall width	b1 (mm)	685
Fork dimensions	s/e/I (mm)	53/160/1150 (1220)
Width overall forks	b5 (mm)	520/550/685
Aisle width for pallets 1000x1200 (1200 crossways)	Ast (mm)	1725/1795
Aisle width for pallets 800x1200 (1200 lengthways)	Ast (mm)	1775/1795
Turning radius	Wa (mm)	1335/1405
Travel speed, laden/unladen	Km/h	4/4.5
Battery voltage/nominal capacity K20	V/Ah	24/105
Battery dimensions I/w/h	mm	260/169/215
Battery weight	Kg	49
Service weight (with battery)	Kg	250

### **P2.0UTE Power Plug Types**















Hyster Company P.O. Box 7006 Greenville, North Carolina 27835-7006 Part No. P2.0UTE/BTG/CARIB 4/2020 Litho in U.S.A.

Visit us online at www.hyster.com or call us at 1-800-HYSTER-1.

Hyster, and STRONG PARTNERS, TOUGH TRUCKS, are registered trademarks in the United States and certain other jurisdictions. Hyster products are subject to change without notice.

Trucks may be shown with optional equipment. @ 2020 Hyster Company. All rights reserved.