



NARROW AISLE REACH TRUCK SERIES

MORE THAN HUMANLY POSSIBLE

Because the shipment arrived late, because the orders just increased, because you're 3 operators short...whatever is happening in your warehouse, you always seem to be asked to do what's more than humanly possible. The newly-designed Hyster® narrow aisle reach trucks are designed to help you do exactly that.

N35-45ZR3, N30-35ZDR3, N35-40ZRS3, N30ZDRS3
3,000-4,500 lb



**MOVE MORE
WITH LESS**



**OPERATOR
COMFORT**



**BEST-IN-CLASS
FORWARD
VISIBILITY**



**SIMPLIFIED
SERVICE**

MEET THE NEW WAREHOUSE WORKHORSE

1 INDUSTRY LEADING LIFT/LOWER CYCLE TIMES WHILE USING LESS ENERGY

Our trucks move more pallets than our competitors while using less energy, helping increase productivity by as much as 7% per truck, per shift, while using up to 20% less energy.†

2 INDUSTRY EXCLUSIVE ERGONOMIC FEATURES

Industry exclusive ergonomic features and pedal-free design provide flexibility within the compartment for a comfortable and natural operating experience.


3 BEST-IN-CLASS FORWARD VISIBILITY

The Hyster reach truck features up to 33% greater visibility through the mast* than leading competitors. This, combined with innovative design features, allows the operator to see the tip of the forks, eliminating guesswork on where to place the load. This helps reduce facility, product and truck damage, while allowing for enhanced precision and speed.

4 SIMPLE AND COST-EFFECTIVE SERVICE

Simplified routine maintenance helps to reduce overall cost of operation by saving you up to \$2500 per truck per year.**



Hyster,  and STRONG PARTNERS. TOUGH TRUCKS. are registered trademarks in the United States and certain other jurisdictions. Hyster products are subject to change without notice. Trucks may be shown with optional equipment. © 2020 Hyster Company. All rights reserved. 4/2020

* Requires the premium or premium 9.4XL mast (N40ZR3, N30ZDR3, N45ZR3, N35ZDR3)

† Competitive comparison data validated through internal testing or customer applications.

** Calculation based on adhering to OEM recommended maintenance intervals and average \$100/hour maintenance labor costs; operating 2000 hours/year.